



The Dankoff Solar Force Piston Pump is the ultra-efficient pump in the Dankoff product line, capable of pumping over long distances directly from a PV panel in low light conditions.

With up to 75% better efficiency over centrifugal or AC pumps, the Solar Force Piston Pump coupled with the Dankoff DC Controller offers unparalleled performance for regions with low light weather patterns for part of the year, and is dirt and dry run tolerant.

Designed for reliability and maintainability, wear parts typically last 5-10 years, with an overall life expectancy of 15-20 years before rebuild.

Pressurizing Application

Though the DC version is most efficient, the AC version uses a low-surge permanent magnet motor that greatly reduces starting surge, inverter size, and wire size requirements (when compared to conventional AC pumps).

Rugged and Reliable

Proven design with a 20-year life expectancy, simple to maintain with common tools (5-10 yr. maintenance interval)

Mechanical Drive

Allows engine or hand-lever backup

Illustrated Instruction Manual

Makes it easy for anyone to install and service, with no previous experience

Voltages Available

- 12, 24, 48 VDC
- 115 V or 230 VAC, 50-60 Hz

Note: PV-Direct full working voltage is typically 20% higher than nominal (example: 29 V for a 24 V system)



Construction

- Cast iron body
- Brass cylinder and valve seats
- Leather cup piston seals
- Neoprene valve seals
- Oil-bath crankcase
- Gear (timing) belt drive on PV models
- Standard V-belt on B models
- Pressure relief valve
- Permanent Magnet DC Motor
- Surge tank included (not in photo)

Suction Capacity

25 vertical feet (7.6 m) at sea level. Subtract 1 foot for every 1000 ft. elevation (1 m for every 1,000 m). Suction capacity may be further limited by intake pipe friction. Intake piping should be minimum 1" (3010, 3020 models) or minimum 1 1/4" (3040). For best reliability, place the pump as close to the water source as possible.

Fittings

- Intake: 1 1/4" female pipe thread
- Outlet: 1" female pipe thread

Solar Surface Pump Technical Data

Dankoff Solar SolarForce Piston Pump



Warranty

2 years against defects in materials and workmanship

System Requirements

- Solar-Direct Systems: Chart indicates power (w) required at the pump. The rated power of the PV array must exceed this number by 20 % or more. A pump controller (linear current booster) is required for the pump to start and run in varying light conditions. A solar tracker may be used to increase daily yield (40-55 % in summer).
- Pressurizing Systems: battery power system, pressure switch, and pressure tank of minimum 60 gallon (230 l) size (captive-air tank, available locally)

Dimensions

- 22 x 13 x 16" high (56 x 33 x 41 cm)
- With Surge Tank (not shown in photo), total height 26" (60 cm)
- Weight, max. 80 lbs (36 kg)
- Shipped in 2 to 3 boxes

Reading the Chart

Total Lift = vertical Distance from surface of the water source to the pipe outlet or top of storage tank

GPM = U.S. Gallons Per Minute

LPM = Liters Per Minute

Model Designation:

V=voltage, **B**=battery model, **PV**=PV array-direct model

| Feet | Total Vertical Lift | | | Model #3010-V-B | | | V = Voltage · Specify 12, 24, 48, 115, 230 AC | | | | | |
|------|---------------------|------|-----------|-----------------|------|-------|---|------|-----------------------|-----|------|-------|
| | Meters | PSI | KG/sq. cm | GPM | LPM | Watts | Model #3020-V-B or PV | | Model #3040-V-B or PV | | | |
| | | | | GPM | LPM | Watts | GPM | LPM | Watts | GPM | LPM | Watts |
| 20 | 6.1 | 8.7 | 0.61 | 5.9 | 22.3 | 77 | 5.2 | 19.7 | 110 | 9.3 | 35.2 | 168 |
| 40 | 12.2 | 17.4 | 1.22 | 5.6 | 21.3 | 104 | 5.2 | 19.7 | 132 | 9.3 | 35.2 | 207 |
| 60 | 18.3 | 26 | 1.83 | 5.3 | 20.2 | 123 | 5.1 | 19.3 | 154 | 9.2 | 34.9 | 252 |
| 80 | 24.4 | 35 | 2.44 | 5 | 19.7 | 152 | 5.1 | 19.3 | 162 | 9.2 | 34.9 | 286 |
| 100 | 30.5 | 43 | 3.05 | 5.1 | 19.2 | 171 | 5 | 18.9 | 202 | 9.1 | 34.5 | 322 |
| 120 | 36.6 | 52 | 3.66 | 4.9 | 19.2 | 200 | 5 | 18.9 | 224 | 9.1 | 34.5 | 364 |
| 140 | 42.7 | 60 | 4.27 | 4.9 | 18.7 | 226 | 5 | 18.9 | 252 | 9.1 | 34.5 | 403 |
| 160 | 48.8 | 70 | 4.88 | | | | 4.9 | 18.6 | 269 | | | |
| 180 | 54.9 | 78 | 5.49 | | | | 4.9 | 18.6 | 280 | | | |
| 200 | 61 | 87 | 6.1 | | | | 4.8 | 18.2 | 308 | | | |
| 220 | 67.1 | 96 | 6.71 | | | | 4.7 | 17.8 | 314 | | | |

Specifications may vary ± 10%

PV Models are measured at 14, 28, or 56V (array direct)