

STORAGE SOLVED



CHOOSE FROM TWO MODELS RGS5100 51.2V 100AH RGS5200 51.2V 200AH



FEATURES

- Touchscreen LCD
- Stack Technology eliminates the need for racking/cabinets
- Enclosed cabling and networking compartment
- Casters for maximum mobility
- 6,000 cycles with 12 yr warranty
- Multiway Closed Loop Comm with inverters
- Integrated RPSD
- Impactive Balancing for up to 30% longer life
- UL9540A pending

THE RUBIX MISSION

To deliver exceptional solar battery systems through practical, hands-on development, excellent service, and strong partnerships with the industry's professionals. Rubix: Built by installers, for installers.

A PRODUCT OF ARK BATTERY & MILLERTECH

Ark Battery: 888-662-7522 MillerTech: 855-629-5484 Email: support@rubixbattery.com

GENERAL SPECIFICATIONS

| | | 205AH, 48V |
|----------------------------------|-----------------|-----------------|
| MODEL NUMBER | RGS51100 | RGS51205 |
| NOMINAL VOLTAGE | 48 | 48 |
| ACTUAL VOLTAGE @20% SOC | 51.2 | 51.2 |
| AMP-HRS | 100 | 205 |
| NAMEPLATE CAPACITY—KWH | 5.12 | 10.5 |
| MAX CONTINUOUS DISCHARGE AMPS | 90 | 140 |
| RECOMMENDED DISCHARGE (MAX AMPS) | 75 | 120 |
| MAX CHARGING AMPS—CONTINUOUS | 70 | 120 |
| PEAK CHARGING AMPS—30 MINUTES | 80 | 140 |
| RATED CYCLE LIFE—100% DOD | 4,000 | 4,000 |
| BATTERY CERTIFICATION | UL9540A PENDING | UL9540A PENDING |
| TRANSPORT CERTIFICATION | UN38.3 | UN38.3 |
| VENTILATION REQUIRED | NO | NO |
| MINIMUM TEMP (DEGRESS F) | 32 | 32 |
| MAXIMUM TEMP (DEGRESS F) | 120 | 120 |
| IP RATING | 50 | 50 |
| BREAKER SIZE (AMPS) | 125 | 150 |
| CELL CHEMISTRY | LIFEP04 | LIFEP04 |
| CELL FORMAT | PRISMATIC | PRISMATIC |
| BALANCING TYPE | IMPACTIVE | IMPACTIVE |
| BATTERY WEIGHT | 117 | 199 |

BOTH BATTERY MODELS USE THE SAME BASE AND LID



